

# SMMSe / SHRMe VRF Indoor Unit MMU-AP0362H2UL—4-Way-Cassette

**TOSHIBA**  
*Carrier*

## Submittal Data

Job Data \_\_\_\_\_ Location \_\_\_\_\_  
 Buyer \_\_\_\_\_ Buyer PO # \_\_\_\_\_ Carrier # \_\_\_\_\_  
 Unit Number \_\_\_\_\_ Model Number \_\_\_\_\_  
 Performance Data Certified By \_\_\_\_\_ Date \_\_\_\_\_



### SMMSe / SHRMe VRF 4-Way Cassette Features

- R-410A refrigerant
- Ten sizes from 7,500 to 42,000 Btu/h
- Optional fresh air intake
- Quiet operation (as low as 31 dBA)
- Standard condensate pump with 26 in. lift capacity
- Independent louver control (fixed or swing)
- Optional wired or wireless controls
- Auto or manually set three fan speeds
- Easy to remove cleanable filter
- Five-year parts limited warranty

INDOOR UNIT MODEL		MMU-AP0362H2UL
<b>PERFORMANCE</b>		
Cooling Rated Capacity	Btu/h	36,000
Heating Rated Capacity	Btu/h	40,000
Fan Type (Qty)	Turbo (1)	
Airflow (L, M, H)	CFM	630 / 840 / 1160
Sound Pressure (L / M / H)	dBA	36.5 / 40.5 / 46
<b>ELECTRICAL</b>		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	kW	0.088
Full Load Amps (FLA)	A	1.0
Minimum Circuit Amps (MCA)	A	1.3
Maximum Overcurrent Protection	A	15
<b>MOTOR</b>		
Motor Type	DC Inverter Driven	
Motor Watts	W	150

PHYSICAL DATA		
Pipe Connection Size - Liquid (High Pressure)	in.	3/8 (Flare)
Pipe Connection Size - Gas (Low Pressure)	in.	5/8 (Flare)
Pipe Connection Size - Drain (OD)	in.	1-1/4
Pipe Connection Size - Drain (ID)	in.	1
Refrigerant	R-410A	
External Finish	Munsell 2.5GY9.0/0.5	
Unit Width	in.	33-1/8
Unit Height	in.	12-5/8
Unit Depth	in.	33-1/8
Unit Net Weight	lb	59
Panel Width	in.	37-3/8
Panel Height	in.	1-3/16
Panel Depth	in.	37-3/8
Panel Net Weight	lb	10

### ACCESSORIES (Optional)

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li><input type="checkbox"/> Wired Remote Controller (7-Day Programmable) RBC-AMS54E-UL</li> <li><input type="checkbox"/> Simple Wired Remote Control RBC-AS41UL</li> <li><input type="checkbox"/> Integral Receiver with Wireless Remote RBC-AX32U(W)-UL</li> <li><input type="checkbox"/> Stand Alone Receiver with Wireless Remote TCB-AX32UL</li> <li><input type="checkbox"/> Remote Sensor TCB-TC41LUL</li> </ul> | <ul style="list-style-type: none"> <li><input type="checkbox"/> Wired Remote Controller RBC-AMT32UL</li> <li><input type="checkbox"/> Grille Panel RBC-U31PG(W)-UL</li> <li><input type="checkbox"/> Spacer for Height Adjustment TCB-SP1602UUL</li> <li><input type="checkbox"/> Air Discharge Direction Kit TCB-BC1602UUL</li> <li><input type="checkbox"/> Fresh Air Chamber TCB-GFC1602UUL</li> <li><input type="checkbox"/> Fresh Air Inlet Box TCB-GB1602UUL</li> <li><input type="checkbox"/> Auxiliary Fresh Air Flange TCB-FF101URUL</li> </ul> |
|--|--|

# DIMENSIONAL DRAWING INDOOR UNIT 4-WAY CASSETTE MMU-AP0362H2UL

