

Indoor Fan Rated Airflow (cfm)

38AU/38AUQ/40RU/40RUQ

Split Systems

6 to 20 Nominal Tons



Airflow Data Supplement

NOTE: Read the entire installation instruction manual before starting installation for the units listed in this supplement.

The data in this supplement details the rated indoor air (cfm) airflow used for the unit AHRI efficiency rating for the following models: 38AUZ with 40RUA, 38AUD with 40RUA, and 38AUQ with 40RUQ.

38AUZ with 40RUA

Model Numbers	Full Load Airflow (cfm)
38AUZ*07 – 40RUA*07	2400
38AUZ*08 – 40RUA*08	3000
38AUZ*12 – 40RUA*12	4000
38AUZ*14 – 40RUA*14	4375
38AUZ*16 – 40RUA*16	6000
38AUZ*25 – 40RUA*25	8300

38AUQ with 40RUQ

Model Numbers	Full Load Airflow (cfm)
38AUQ*07 – 40RUQ*07	2400
38AUQ*08 – 40RUQ*08	3000
38AUQ*12 – 40RUQ*12	3000
38AUQ*16 – 40RUQ*16	6000
38AUQ*25 – 40RUQ*25	7400

38AUD with 40RUA

Model Numbers	Full Load Airflow (cfm)
38AUD*12 – 40RUA*12	4000
38AUD*14 – 40RUA*14	4400
38AUD*16 – 40RUA*16	6000
38AUD*25 – 40RUA*25	8300