

Ducted Style Heat Pump Ductless System



Indoor Model: RAV-SP241BT-UL
Outdoor Model: RAV-SP240AT2-UL

turn to the experts™

Submittal Data

Job Data: _____ Location: _____

Buyer: _____ Buyer P.O. #: _____ Carrier #: _____

Unit Number: _____ Model Number: _____

Performance Data Certified By: _____ Date: _____



DUCTED UNIT STANDARD FEATURES

- Digital inverter compressor technology
- Built-in Condensate pump (21.7 in of lift from bottom of unit)
- System can operate in cooling-only mode with heating locked out
- 3 indoor unit fan speeds
- Power saving mode
- Quiet operation
- Low-ambient cooling down to 0°F*
- System diagnostics
- Rear or bottom return
- Outside Air Intake

* With wind baffles installed

CONTROL FEATURES

- Optional wireless remote control
- Optional wired remote control

(Unless otherwise indicated, data applies to both indoor and outdoor models)

SYSTEM SIZE	24
REFRIGERANT	R-410A
PERFORMANCE	
Rated Cooling Capacity (Btuh)	24,000
Cooling Range (Btuh)	14,000-28,500
SEER/EER	18.2/9.6
Rated Heating Capacity (Btuh)	27,000
Heating Range (Btuh)	19,800-30,800
HSPF	9.6
AIRFLOW (DRY)	
Indoor Airflow H / M / L (cfm)	706/618/529
Max Static Pressure (in. WG)	0.45
Sound Pressure - dBA	
Outdoor Sound Pressure (dBA)	49/50
Indoor Sound Pressure at different speeds (dBA)	36/34/32

ELECTRICAL	
System Voltage	208/230-1-60
Indoor Unit	Wired from Outdoor
Wires between Indoor and Outdoor	4
MCA	24
MOCP	40
CONTROLS	
Wireless Remote	Optional
Wired Control	Optional
REFRIGERANT LINES	
Total Piping Length (ft)	165
Vertical Lift (ft)	100
Suction Line Size (in)	5/8
Liquid Line Size (in)	3/8
AMBIENT OPERATING RANGE	
Cooling DB Min ~ Max (F)	23~115 (0 with wind baffle)
Heating DB Min ~ Max (F)	-4~59
UNIT WEIGHT - Gross/Net	
Indoor unit (lbs)	104/93
Outdoor unit (lbs)	157/144.5

