

DUCTLESS SYSTEMS

DURACOMFORT™ SERIES

DLFLCA CASSETTE



OUTDOOR FEATURES

- Available in 208/230V
- Up to 17.5 SEER and 11.0 HSPF when paired with DLCLRA outdoor unit
- Modes: Cool, Heat, Dry, Fan, Auto
- Auto-restart function
- Louver control (fixed or swing)
- Three fan speeds
- Outside air intake
- Built-in condensate lift pump
- Follow Me (senses temperature at handheld remote)
- Heating Setback (46° F Heating Mode)
- Quiet indoor operation, as low as 49 dB(A)
- Aluminum Golden Hydrophilic pre-coated fins
- Grille/ceiling panel 3' x 3' P/N KSALG0201AAA

COMPATIBLE WITH:

- DLCLRA Outdoor Unit Single Zone

Optimal Air Distribution & Light Commercial Comfort Control

Sizes: 36 / 48

KEY FEATURES

Built-In Condensate Lift Pump

The Cassette is supplied with a condensate lift pump that is capable of lifting the water 29.5 in. (750 mm.) above the top of the unit.

360° Air Flow Panel

With the 360° air flow panel, air is distributed to every corner of the room.

CONTROLS

Wireless Remote Controller included with indoor unit

Optional Wired Remote Controller KSACN0101AAA (Timer Function)

Optional Wired Remote Controller KSACN0501AAA (7-Day Programmable)



**Wired Controller
(7-Day Programmable)
KSACN0501AAA**




**Wireless Remote
Controller**

ACCESSORIES

Wi-Fi® Kit KSAIF0401AAA



NOTE: Grille is required; sold separately.



DUCTLESS SYSTEMS

DURACOMFORT™ SERIES

DLFLCA CASSETTE

SPECIFICATIONS:

DLFLCA Cassette			
Heat Pump System			
Size		36	48
Indoor Model		DLFLCAH36XAK	DLFLCAH48XAK
Electrical			
Voltage-Phase-Cycle		V-Ph-Hz	208/230-1-60
Power Supply		Indoor unit powered from outdoor unit	
MCA		A.	0.8
		1.6	
Operating Range			
Cooling Indoor DB Min - Max		° F (° C)	63~90 (17~32)
Heating Indoor DB Min - Max		° F (° C)	32~86 (0~30)
		32~86 (0~30)	
Piping			
Pipe Connection Size - Liquid		in (mm)	3/8 (9.52)
Pipe Connection Size - Suction		in (mm)	5/8 (16)
		5/8 (16)	
Indoor			
Body Unit Width		in (mm)	33.07 (840)
Body Unit Height		in (mm)	9.65 (245)
Body Unit Depth		in (mm)	33.07 (840)
Body Net Weight		lbs (kg)	58.2 (26.4)
Panel Unit Width			37.4 (950)
Panel Unit Height		in (mm)	2.17 (55)
Panel Unit Depth		in (mm)	37.4 (950)
Panel Net Weight		lbs (kg)	11.02 (5)
Number of Fan Speeds			3
Airflow (lowest to highest)		CFM	809/958/1095
Sound Pressure (lowest to highest)		dB(A)	49/52/55
Air Throw Data		ft (m)	30 (9)
Moisture Removal		Pint/h (L/h)	8.53 (4.04)
Field Drain Pipe Size O.D.		in (mm)	1 (25.4)
			1 (25.4)

COMPATIBILITY:

Indoor Unit	DLFLCAH36XAK	DLFLCAH48XAK
Outdoor Unit Single Zone*	DLCLRAH36AAK	DLCLRAH48AAK

*Performance may vary based on the compatible outdoor units. See respective pages for performance data.

Manufacturer reserves the right to discontinue, or change at any time, specification or designs without notice or incurring obligations.