



United Technologies

Premor[®]



Islands

Benefits at a glance



- Promotion in view
- Excellent product visibility and quick orientation
- High storage capacity for chilled and frozen food
- Attractive and robust design

Premor[®]

Plug-in freezer & switchable island for promotional sales


Standard configuration

- Internal and external panels galvanized steel with hard-wearing NCS 0501-B58G white powder coated finish
- Electronic control inclusive temperature readout
- Temperature-assured air-forced cooling with honeycomb air outlet
- Electronic controller
- Automatic defrost with drip water evaporation
- Energy-saving fan with reverse function for condenser
- Energy-saving sliding glass lids
- LED handrail lighting
- Wire shelves (switchable)



Premor 2060/80 G

Basic models



	Units	Natural						
		1080 G	1580 G	2080 G	1060/80 G	1560/80 G	2060/80 G	
Temperature	[°C]	-22...-24			-2...0 -22...-24	-1...+1 -22...-24	0...+2 -22...-24	
Refrigerant		R290			R290			
Width	[mm]	930	1545	2095	930	1545	2095	
Depth	[mm]	915	930	930	915	930	930	
Height	[mm]	915			915			
Volume								
Freezer mode	[l]	158	317	453	158	317	453	
Chiller mode					52	109	157	
Power consumption ref.	[W]	470	930	1036	470	930	1036	
Power consumption def.	[W]	543	1139	1217	543	1139	1282	
Energy consumption*								
Freezer mode	[kWh/d]	9.4	17.4	22.0	9.4	17.4	22.0	
Chiller mode					6.3	10.5	15.5	
Heat dispatch*								
Freezer mode	[W]	392	725	917	392	725	917	
Chiller mode					263	376	646	
Application								

* at Climate Class 3 according to ISO 23953



Carrier Commercial Refrigeration is a leading supplier of high-efficiency turnkey refrigeration systems and services in the food retail industry.

www.carrier-refrigeration.com
www.carrier.com

