



United Technologies

# Optimer<sup>®</sup> Low Front



Multidecks

## Benefits at a glance

- Consistent store layout
- Improved energy efficiency
- Enlarged product-facing area
- Multiplexible
- Four available lengths



# Optimer<sup>®</sup> Low Front

Refrigerated Plug-in multideck with maximized display area



## Standard configuration

- Internal and external panels galvanized steel with hard-wearing RAL9003 white powder-coated finish
- Panorama endwalls
- Integrated front bumper
- Temperature-assured forced-air cooling with honeycomb air outlet
- Energy saving fans
- 5 Display shelves with 40 mm scanner price rails
- Horizontal lighting T5 (R404A) or LED (R290)
- Manual nightblind or double tempered glass doors
- Electronic controller
- Slideable condensing unit for easy service



Optimer 1348 LG

## Basic models



		Natural						Standard			
		1348 L **	1948 L	0948 LG	1348 LG	1948 LG	2548 LG ***	0948 L	1348 L	1948 L	2548 L
Temperature	[°C]	0...+2		-1...+1				0...+2			
Refrigerant		R290						R404A			
Width	[mm]	1250	1875	885	1250	1875	2420	885	1250	1875	2420
Depth	[mm]	840						840			
Height	[mm]	2040						2040			
Volume	[l]	716	1102	570	716	1102	1436	485	716	1102	1436
Power consumption ref.	[W]	–	2177	485	679	1238	1358	1074	1296	1952	2557
Power consumption def.	[W]	–	673	452	512	704	1024	453	491	673	950
Energy cons.* (12 h light and blind)	[kWh/d]	–	25.6	8.3	12.0	16.9	24	16.0	19.2	28.1	35.8
Heat dispatch*	[W]	–	1067	346	500	704	1000	667	800	1171	1492
Application											

\* at Climate Class 3 according to ISO 23953 | \*\* under preparation | \*\*\* 2x1348 LG cabinet multiplexed



Carrier Commercial Refrigeration is a leading supplier of high-efficiency turnkey refrigeration systems and services in the food retail industry.

[www.carrier-refrigeration.com](http://www.carrier-refrigeration.com)  
[www.carrier.com](http://www.carrier.com)

