

Contactors

Overview

All purpose electric door switch. Knockouts on top, bottom and rear.

Applications

Closet lights, dark rooms, walk-in refrigerators. For sliding or hinged doors.

Ordering Information

Cat. No.	Description	Contact Ratings		Dimensions		
		Volts	AC Amps	H	W	D
502A	Depress plunger to open circuit	125	6	4 (102)	1-1/2 (38)	1-3/4 (44)
503A	Depress plunger to close circuit	125	6	4 (102)	1-1/2 (38)	1-3/4 (44)

Switch faceplate has mounting holes on 3-1/4" centres.



Door Light Switch

502A, 503A

Overview

Non-insulated, external mounting. Makes and breaks as door opens. Zinc plated.

Applications

Signals entry into stores, offices, etc.

Ordering Information

Cat. No.	Dimensions		
	L	W	D
236	1-1/4" (32mm)	1-5/16" (33mm)	3-1/4" (82mm)



Door Trip

236

Overview

Wide range of low voltage applications. Insulated, construction for long service life. Easily operated from pressure in any direction. Fast installation.

Applications

Doors, windows, transoms, burglar alarms, machinery.

Ordering Information

Cat. No.	Description	Contact Ratings			Hole	Depth Overall
		Volts	AC Amps	DC Amps		
44	Push to open contacts					
45	Push to close contacts	12	2	2	13/16 (20)	1-1/8 (28)
		24	2	1		
46E	Push to make then break and repeat on return	48	1	.5		



Rolling Ball Contactor

44, 45, 46E